

## Folding Thermocouple Thermometer

**Model: TCT572-W (White), TCT572-BK (Black), TCT572-R (Red)**

Compact folding thermocouple with rapid response and 1.5 mm thin tip probe. Field recalibratable. Stores minimum/maximum temperatures and is extremely durable.



Features	Maximum and minimum, backlit, extra big digit, on/off switch
Measurement Range	-58 to +572°F/-50 to +300°C
Unit of Measure	°F/°C
Accuracy	±2°F
Calibration	Field calibration
Water Resilience	IPX4: protected from splashing of water for 10 minutes (except case/probe junction)
Response Time	3-6 second response
On/Off	On/off button
Auto-off	Auto-off after 10 minutes
Housing Material	Food-safe ABS
Display Material	LCD
Display Size	1.875 W x 0.75 H (in)/4.8 W x 1.9 H (cm)
Probe Type	Thermocouple Type K
Probe Material	304 stainless steel
Probe Length	4.25"/10.8 cm
Sensor Diameter	1.5 thin tip
Resolution	0.1°F/0.1°C
Operating Range	32 to 104°F/0 to 40°C/≤90% RH
Battery	Two CR2032 lithium button batteries included
Battery Life	404 days
Dimensions	1.625 W x 2.25 H x 0.5 D (in)/4.1 W x 5.7 H x 1.3 D (cm)
Weight	2.4 oz / 68 g (including battery)
UPC	TCT572-W: 0 18436 00464 6, TCT572-BK: 0 18436 00465 3, TCT572-R: 0 18436 00466 0
Certification	NSF <sup>®</sup> Certified, WEEE, CE
Antimicrobial Protection	BioCote <sup>®</sup>
Warranty	5-Year Limited Warranty