




## **Beverage & Frothing Thermometer** – 6.5" Stem

Model: IRB220-F-6.5, IRB220-F-6.5-C (Celsius)





Measurement Range       0 to 220°F/-18 to +104°C         Unit of Measure       °F/°C         Accuracy       ±2°F         Calibration       Field calibration         Water Resilience       Safe for commercial dishwashers         Response Time       15 second response (approximate)         Housing Material       304 stainless steel         Display Material       Shatterproof lens         Display Size       1.5"/3.8 cm dial         Probe Type       Bimetal         Probe Type       Bimetal         Probe Length       6.5"/16.5 cm stem         Probe Diameter       3 mm tip         Resolution       2"F/1"C         Vessel Clip       Adjustabe stainless steel clip AD-N         Casing       Sheath         Mounting       Pocket clip         Dimensions       1.5 W x 7 H x 1.5 D (in)/3.8 W x 17.8 H x 3.8 D (cm)         Weight       1.1cz / 31.2 g         UPC       IRB220-F-6.5: 0 18436 00235 2, IRB220-F-6.5-C: 0 18436 00732 6         Certification       NSF® Certified         Antimicrobial Protection       BioCote®         Warranty       5-Year Limited Warranty         Optional Accessories       AD-N	Features	Color-coded frothing zone
Accuracy         ±2°F           Calibration         Field calibration           Water Resilience         Safe for commercial dishwashers           Response Time         15 second response (approximate)           Housing Material         304 stainless steel           Display Material         Shatterproof lens           Display Size         1.5"/3.8 cm dial           Probe Type         Bimetal           Probe Adterial         304 stainless steel           Probe Length         6.5"/16.5 cm stem           Probe Diameter         3 mm tip           Resolution         2°F/1°C           Vessel Clip         Adjustabe stainless steel clip AD-N           Casing         Sheath           Mounting         Pocket clip           Dimensions         1.5 W x 7 H x 1.5 D (in)/3.8 W x 17.8 H x 3.8 D (cm)           Weight         1.1oz / 31.2 g           UPC         IRB220-F-6.5: 0 18436 00235 2, IRB220-F-6.5-C: 0 18436 00732 6           Certification         NSF® Certified           Antimicrobial Protection         BioCote®           Warranty         5-Year Limited Warranty	Measurement Range	0 to 220°F/-18 to +104°C
Calibration Field calibration  Water Resilience Safe for commercial dishwashers  Response Time 15 second response (approximate)  Housing Material 304 stainless steel  Display Material Shatterproof lens  Display Size 1.5"/3.8 cm dial  Probe Type Bimetal  Probe Material 304 stainless steel  Probe Length 6.5"/16.5 cm stem  Probe Diameter 3 mm tip  Resolution 2°F/1°C  Vessel Clip Adjustabe stainless steel clip AD-N  Casing Sheath  Mounting Pocket clip  Dimensions 1.5 W x 7 H x 1.5 D (in)/3.8 W x 17.8 H x 3.8 D (cm)  Weight 1.1oz / 31.2 g  UPC IRB220-F-6.5: 0 18436 00235 2, IRB220-F-6.5-C: 0 18436 00732 6  Certification NSF° Certified  Antimicrobial Protection BioCote®  Warranty 5-Year Limited Warranty	Unit of Measure	°F/°C
Water Resilience       Safe for commercial dishwashers         Response Time       15 second response (approximate)         Housing Material       304 stainless steel         Display Material       Shatterproof lens         Display Size       1.5"/3.8 cm dial         Probe Type       Bimetal         Probe Material       304 stainless steel         Probe Length       6.5"/16.5 cm stem         Probe Diameter       3 mm tip         Resolution       2°F/1°C         Vessel Clip       Adjustabe stainless steel clip AD-N         Casing       Sheath         Mounting       Pocket clip         Dimensions       1.5 W x 7 H x 1.5 D (in)/3.8 W x 17.8 H x 3.8 D (cm)         Weight       1.10z / 31.2 g         UPC       IRB220-F-6.5: 0 18436 00235 2, IRB220-F-6.5-C: 0 18436 00732 6         Certification       NSF® Certified         Antimicrobial Protection       BioCote®         Warranty       5-Year Limited Warranty	Accuracy	±2°F
Response Time 15 second response (approximate) Housing Material 304 stainless steel Display Material Shatterproof lens Display Size 1.5"/3.8 cm dial Probe Type Bimetal Probe Material 304 stainless steel Probe Length 6.5"/16.5 cm stem Probe Diameter 3 mm tip Resolution 2°F/1°C Vessel Clip Adjustabe stainless steel clip AD-N Casing Sheath Mounting Pocket clip Dimensions 1.5 W x 7 H x 1.5 D (in)/3.8 W x 17.8 H x 3.8 D (cm) Weight 1.1oz / 31.2 g UPC IRB220-F-6.5: 0 18436 00235 2, IRB220-F-6.5-C: 0 18436 00732 6 Certification NSF® Certified Antimicrobial Protection BioCote® Warranty 5-Year Limited Warranty	Calibration	Field calibration
Housing Material 304 stainless steel  Display Material Shatterproof lens  Display Size 1.5"/3.8 cm dial  Probe Type Bimetal  Probe Material 304 stainless steel  Probe Length 6.5"/16.5 cm stem  Probe Diameter 3 mm tip  Resolution 2°F/1°C  Vessel Clip Adjustabe stainless steel clip AD-N  Casing Sheath  Mounting Pocket clip  Dimensions 1.5 W x 7 H x 1.5 D (in)/3.8 W x 17.8 H x 3.8 D (cm)  Weight 1.1oz / 31.2 g  UPC IRB220-F-6.5: 0 18436 00235 2, IRB220-F-6.5-C: 0 18436 00732 6  Certification NSF® Certified  Antimicrobial Protection BioCote®  Warranty 5-Year Limited Warranty	Water Resilience	Safe for commercial dishwashers
Display Material  Display Size  1.5"/3.8 cm dial  Probe Type  Bimetal  Probe Material  304 stainless steel  Probe Length  6.5"/16.5 cm stem  Probe Diameter  3 mm tip  Resolution  2°F/1°C  Vessel Clip  Adjustabe stainless steel clip AD-N  Casing  Sheath  Mounting  Pocket clip  Dimensions  1.5 W x 7 H x 1.5 D (in)/3.8 W x 17.8 H x 3.8 D (cm)  Weight  1.1oz / 31.2 g  UPC  IRB220-F-6.5: 0 18436 00235 2, IRB220-F-6.5-C: 0 18436 00732 6  Certification  NSF® Certified  Antimicrobial Protection  BioCote®  Warranty  5-Year Limited Warranty	Response Time	15 second response (approximate)
Display Size 1.5"/3.8 cm dial  Probe Type Bimetal  Probe Material 304 stainless steel  Probe Length 6.5"/16.5 cm stem  Probe Diameter 3 mm tip  Resolution 2°F/1°C  Vessel Clip Adjustabe stainless steel clip AD-N  Casing Sheath  Mounting Pocket clip  Dimensions 1.5 W x 7 H x 1.5 D (in)/3.8 W x 17.8 H x 3.8 D (cm)  Weight 1.1oz / 31.2 g  UPC IRB220-F-6.5: 0 18436 00235 2, IRB220-F-6.5-C: 0 18436 00732 6  Certification NSF® Certified  Antimicrobial Protection BioCote®  Warranty 5-Year Limited Warranty	Housing Material	304 stainless steel
Probe Type Bimetal  Probe Material 304 stainless steel  Probe Length 6.5"/16.5 cm stem  Probe Diameter 3 mm tip  Resolution 2°F/1°C  Vessel Clip Adjustabe stainless steel clip AD-N  Casing Sheath  Mounting Pocket clip  Dimensions 1.5 W x 7 H x 1.5 D (in)/3.8 W x 17.8 H x 3.8 D (cm)  Weight 1.1oz / 31.2 g  UPC IRB220-F-6.5: 0 18436 00235 2, IRB220-F-6.5-C: 0 18436 00732 6  Certification NSF® Certified  Antimicrobial Protection BioCote®  Warranty 5-Year Limited Warranty	Display Material	Shatterproof lens
Probe Material 304 stainless steel Probe Length 6.5"/16.5 cm stem Probe Diameter 3 mm tip Resolution 2°F/1°C Vessel Clip Adjustabe stainless steel clip AD-N Casing Sheath Mounting Pocket clip Dimensions 1.5 W x 7 H x 1.5 D (in)/3.8 W x 17.8 H x 3.8 D (cm) Weight 1.1oz / 31.2 g UPC IRB220-F-6.5: 0 18436 00235 2, IRB220-F-6.5-C: 0 18436 00732 6 Certification NSF® Certified Antimicrobial Protection BioCote® Warranty 5-Year Limited Warranty	Display Size	1.5"/3.8 cm dial
Probe Length 6.5"/16.5 cm stem  Probe Diameter 3 mm tip  Resolution 2°F/1°C  Vessel Clip Adjustabe stainless steel clip AD-N  Casing Sheath  Mounting Pocket clip  Dimensions 1.5 W x 7 H x 1.5 D (in)/3.8 W x 17.8 H x 3.8 D (cm)  Weight 1.1oz / 31.2 g  UPC IRB220-F-6.5: 0 18436 00235 2, IRB220-F-6.5-C: 0 18436 00732 6  Certification NSF® Certified  Antimicrobial Protection BioCote®  Warranty 5-Year Limited Warranty	Probe Type	Bimetal
Probe Diameter 3 mm tip  Resolution 2°F/1°C  Vessel Clip Adjustabe stainless steel clip AD-N  Casing Sheath  Mounting Pocket clip  Dimensions 1.5 W x 7 H x 1.5 D (in)/3.8 W x 17.8 H x 3.8 D (cm)  Weight 1.1oz / 31.2 g  UPC IRB220-F-6.5: 0 18436 00235 2, IRB220-F-6.5-C: 0 18436 00732 6  Certification NSF® Certified  Antimicrobial Protection BioCote®  Warranty 5-Year Limited Warranty	Probe Material	304 stainless steel
Resolution 2°F/1°C  Vessel Clip Adjustabe stainless steel clip AD-N  Casing Sheath  Mounting Pocket clip  Dimensions 1.5 W x 7 H x 1.5 D (in)/3.8 W x 17.8 H x 3.8 D (cm)  Weight 1.1oz / 31.2 g  UPC IRB220-F-6.5: 0 18436 00235 2, IRB220-F-6.5-C: 0 18436 00732 6  Certification NSF® Certified  Antimicrobial Protection BioCote®  Warranty 5-Year Limited Warranty	Probe Length	6.5"/16.5 cm stem
Vessel Clip Adjustabe stainless steel clip AD-N  Casing Sheath  Mounting Pocket clip  Dimensions 1.5 W x 7 H x 1.5 D (in)/3.8 W x 17.8 H x 3.8 D (cm)  Weight 1.1oz / 31.2 g  UPC IRB220-F-6.5: 0 18436 00235 2, IRB220-F-6.5-C: 0 18436 00732 6  Certification NSF® Certified  Antimicrobial Protection BioCote®  Warranty 5-Year Limited Warranty	Probe Diameter	3 mm tip
Casing         Sheath           Mounting         Pocket clip           Dimensions         1.5 W x 7 H x 1.5 D (in)/3.8 W x 17.8 H x 3.8 D (cm)           Weight         1.1oz / 31.2 g           UPC         IRB220-F-6.5: 0 18436 00235 2, IRB220-F-6.5-C: 0 18436 00732 6           Certification         NSF® Certified           Antimicrobial Protection         BioCote®           Warranty         5-Year Limited Warranty	Resolution	2°F/1°C
Mounting         Pocket clip           Dimensions         1.5 W x 7 H x 1.5 D (in)/3.8 W x 17.8 H x 3.8 D (cm)           Weight         1.1oz / 31.2 g           UPC         IRB220-F-6.5: 0 18436 00235 2, IRB220-F-6.5-C: 0 18436 00732 6           Certification         NSF® Certified           Antimicrobial Protection         BioCote®           Warranty         5-Year Limited Warranty	Vessel Clip	Adjustabe stainless steel clip AD-N
Dimensions       1.5 W x 7 H x 1.5 D (in)/3.8 W x 17.8 H x 3.8 D (cm)         Weight       1.1oz / 31.2 g         UPC       IRB220-F-6.5: 0 18436 00235 2, IRB220-F-6.5-C: 0 18436 00732 6         Certification       NSF® Certified         Antimicrobial Protection       BioCote®         Warranty       5-Year Limited Warranty	Casing	Sheath
Weight 1.1oz / 31.2 g  UPC IRB220-F-6.5: 0 18436 00235 2, IRB220-F-6.5-C: 0 18436 00732 6  Certification NSF® Certified  Antimicrobial Protection BioCote®  Warranty 5-Year Limited Warranty	Mounting	Pocket clip
UPC IRB220-F-6.5: 0 18436 00235 2, IRB220-F-6.5-C: 0 18436 00732 6  Certification NSF® Certified  Antimicrobial Protection BioCote®  Warranty 5-Year Limited Warranty	Dimensions	1.5 W x 7 H x 1.5 D (in)/3.8 W x 17.8 H x 3.8 D (cm)
Certification NSF® Certified  Antimicrobial Protection BioCote®  Warranty 5-Year Limited Warranty	Weight	1.1oz / 31.2 g
Antimicrobial Protection BioCote®  Warranty 5-Year Limited Warranty	UPC	IRB220-F-6.5: 0 18436 00235 2, IRB220-F-6.5-C: 0 18436 00732 6
Warranty 5-Year Limited Warranty	Certification	NSF® Certified
	Antimicrobial Protection	BioCote®
Optional Accessories AD-N	Warranty	5-Year Limited Warranty
	Optional Accessories	AD-N

